



8K H.265 NVR with Facial Recognition and Smart Analytics

N8NRX

8-Channel Facial Recognition
NVR with 8 Built-In PoE Ports

N16NRX

16-Channel Facial Recognition
NVR with 16 Built-In PoE Ports

Product Summary

With Speco's NDAA compliant NRX recorder, you will take your footage quality to the next level now supporting up to 16MP cameras @ 30 fps.

Features

- Real time recording up to 16MP resolution (8K) @ 30fps
- H.265 compression - Store up to 2x more than H.264!
- 4K HDMI out and one VGA monitor output,
- N8NRX: 1 SATA port for up to 20TB of storage max
N16NRX: 2 SATA ports for up to 40TB of storage max
- Facial Recognition and Comparison**
- Object and line crossing detection and alerts*
- Smart Search - Specify a region on the camera view and search on changes in that area*
- Free US-based DDNS and P2P services
- Remote viewing via web browser, or your mobile device
- Easy video exporting via USB
- Remote control included
- Rack ears (N16NRX only)
- 5 year limited warranty

*With Speco Smart Analytic Cameras

**With Speco Facial Detection Cameras

Compatible Apps



One app to view your Speco Devices on the go (Speco Silver Line not supported at this time).



Access your NR and HR Series Recorder to view and playback videos from your camera.



Front panel (N16NRX shown)



Rear panel (N16NRX shown)



Rear panel (N8NRX shown)



specoaccess immix



Included Accessories



Rack Ears



Remote
Look may vary

Optional Accessories



P4S50
5-port IP65 Rated
4 port PoE Switch



P8S10G
10-Port Gigabit Network
Switch (8 ports PoE, 2
ports uplink)



P4S5V
5-Port Gigabit Network
Switch (4 ports PoE,
1 port uplink)



P24S26G2
26-Port Gigabit Switch
with 24-PoE Ports and
2 SFP Uplink



P32S36GM
36 Port Managed
Gigabit Switch
(32 ports PoE, 4xSFP Uplink)

Storage: 2TB - 20TB	
N8NRX2TB	N8NRX12TB
N8NRX4TB	N8NRX16TB
N8NRX6TB	N8NRX20TB
N8NRX8TB	

Storage: 2TB - 40TB	
N16NRX2TB	N16NRX16TB
N16NRX4TB	N16NRX24TB
N16NRX6TB	N16NRX32TB
N16NRX8TB	N16NRX40TB
N16NRX8TB	

Technical Specification NVR Video Recorder

Model		NRX	
Video	Input	Max. IP Channels	8
		IP Camera	H.265/H.264 auto detection (max. 16MP)
	Output	Main Monitor	HDMI (max. 4K) and VGA (max. full HD)
Audio	Network Input		8-CH IPC audio input
	Local Input		RCAx1
	Local Output		RCAx1
Recording	Encoding Resolutions		16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P
	Codec		H.264/H.265 (auto detection)
	Max Frame Rate per Channel		16MP @ 30fps
	Recording Mode		Analytics/continuous/motion/sensor/schedule/manual
	Pre-Recording		Max. 5 seconds
	Post Recording		Max. 10 minutes
Search & Playback	Search		EZ search, motion, specific date/time, event, museum, bookmarks, snapshots, log
	Simultaneous Playback		Max. 8-CH
	Smart Search		Highlighted color to display camera records in a certain period of time, different colors refer to different record events
	Playback Functions		Play, pause, fast forward, rewind, digital zoom, etc.
Backup	Media		USB drive, network
	Format		MP4, JPG, AVI, proprietary format (player included)
Storage	HDD	Max Capacity of each HDD	40TB
		Internal SATA ports	1
	USB	Front	1 (USB 2.0)
		Rear	1 USB 3.0 1 USB 2.0
Alarm	Mode		Manual, sensor, motion, exception, intelligence
	Input		8-CH local
	Output		4-CH local
	Linkage		Record/snapshot/preset/email/pop-up window
User I/F	Input Method		IR remote, mouse
Network	Network Bandwidth		160Mbps
	P2P/Dynamic DNS		Free US-Based Speco P2P and DDNS service
	Network Protocols		TCP/IP, PPPoE, DHCP, DNS, UPnP, NTP, SMTP
Network Access	Mobile		iOS®/Android™ via Speco Blue App, SecureGuard® Client
	Web Viewer		Google Chrome®, Microsoft Edge®, Firefox®, Safari®
	VMS/CMS		Speco Blue VMS, SecureGuard®
	Max. User Access		Max 10 users online (web client)
Features	Digital Zoom		Live and playback, free size
	Fisheye Dewrapping*		Yes
	S.M.A.R.T (Self-Monitoring, Analysis & Reporting Technology)		Temperature, power on time, bad sectors, and health
Smart Analytics	People/Vehicle Detection		Line crossing and intrusion
	Facial Recognition		Face search up to 8-CH (N8NRX) and up to 16-CH (N16NRX) Face recognition trigger event up to 6-CH
	LPR		8-CH
Power	Power Consumption		≤ 15W (without HDD)
	PoE Ports		8
	Power per PoE Port Max (802.3at)		30W
	Total PoE Power Budget (802.3af/at)		80W
Environment	Operating Temperature		14°F to 122°F (-10°C to 50°C)
	Operating Humidity		10% - 90% humidity
Dimensions	Unit		300mm x 249mm x 45mm (11.8" x 9.8" x 2.0")



Products are in compliance with NDAA Section 889 Part B Guidelines. Google Chrome® and Firefox® use Java™ which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™, Google Play® and the Google Play logo® are trademarks of Google Inc. Amazon® is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 12/3/24

