



4MP IP Turret Camera with AI, Audio & Visual Deterrent, NDAA Compliant

O4TDD2M

2.8-12mm motorized lens, white housing

Features

- Captures up to 4MP @ 30fps real time
- Built-in speaker with preset and custom sounds provides audio deterrence
- Built-in high-power red and blue lights provides visual deterrence
- White LED and IR range: up to 164' (depending on scene reflection)
- True WDR operation
- Micro SD card slot (card not included)
- ONVIF Profile G/S/T Compliant
- IP66 Weather Resistance
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting /Intrusion detection*
- Face/Person/Vehicle detection*
- Junction box included (works with NPT/BSP specifications)
- 5 year warranty
- NDAA Compliant**

*with compatible Speco recorder

**Products are in compliance with NDAA Section 889 Part B Guideline



Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS
Maximum Resolution	2592 x 1520 (4MP)
Field of View	Horizontal: 96°- 32.3°, Vertical: 53.47°-19.6°, Diagonal: 114°-36°
Minimum Illumination	0.02lux @ F1.4(AGC ON) ; 0 lux @ LED ON
White Balance	Auto, Indoor, Outdoor, Manual
Compensation	True WDR (120dB), BLC, HLC
Day/Night	Smart IR or supplemental White LED
Electronic Shutter Speed	1/3s - 1/100000s
Angle Adjustment	Pan: 0° - 360°; Tilt: 0° - 75°; Rotation: 0° - 360°

Interfaces

Ethernet	RJ45 Jack, 10/100 Mbps, PoE
Power	12VDC input jack
Audio Input	Built-in mic, 3.5mm input
Audio Output	Built-in speaker, 3.5mm output
Card slot	MicroSD, up to 256GB (not included)
Alarm	1-CH alarm in, 1-CH alarm out
Reset	Yes

Client Specifications

Web Browser Support	Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari
PC Application	SecureGuard' VMS and SecureGuard' CMS
Mobile	SecureGuard' Client, Speco Blue

Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 10 simultaneous users

Audio Specifications

Audio Compression	G.711A / G.711U
-------------------	-----------------

Other Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, Object abandoned/missing detection, region entrance/exiting/intrusion detection (face/people/vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection.
Alarm Triggers	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable discon- nection
Alarm Events	FTP upload, email upload
Image Settings	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction



Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	12.0W (max)
Operating Temperature	-40°F - 140°F
Operating Humidity	less than 95% (non-condensing)
Unit Dimensions	5.125"Ø x 4.1"(H)
Unit Weight	1.48 lb.
Certifications	FCC, ONVIF Profile G/S/T

Video Specifications

Main Resolution	2592x1520, 2560x1440 2304x1296, 1920x1080, 1280x720, D1, CIF, 480x240 @ 30fps
Substream	1280x720, D1, CIF @ 30fps
Third Stream	D1, CIF, 480x240 @30fps
Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
Bitrate Control	VBR, CBR (64Kbps - 8Mbps)
Multiple Streaming	3 streams
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Exposure, Gain, Corridor Pattern, Image flip/mirror

Cameras Interfaces

3.5mm
Audio In



3.5mm
Audio Out



Built-in
Mic



Built-in
Speaker




DC 12V



RJ45
PoE



Alarm In/Out



Optional Accessories



POEINJ
25.5W
PoE Injector



PSW5
12VDC
Power Supply



CMT1
Corner Mount



PMT1
Pole Mount



CLT4
Ceiling Mount



O4D6WM
Wall Mount



CLTX1
Ceiling Mount
4" Extension

NDA
COMPLIANT

ONVIF® | GST



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 8/16/24

