

SP5MAT 5.25" speaker, off-white housing

SP6MAT 6.5" speaker, off-white housing

SP5MATB 5.25" speaker, black housing

SP5MATB 6.5" speaker, black housing

Features

- ABS flame retardant back can
- Easy select transformer dial
- 25V or 70V selector switch
- Safety loop for additional mounting security
- Ported bass
- NDAA Compliant*



Sold
individually

Grilles included for
both models >



Speaker Specifications

Model	SP5MAT/SP5MATB	SP6MAT/SP6MATB
RMS Power	30W	40W
Max Output Power	60W	80W
Transformer Type	70/25V (selectable)	70/25V (selectable)
Transformer Power Taps	30W, 15W, 7.5W, 2.5W, 1W, 0.5W, 0.25W, & 8 Ohms	40W, 30W, 15W, 7.5W, 5W, 2.5W, 1W, 0.5W, 0.25W, & 8 Ohms
Termination Type	Press Terminal	
Sensitivity (1W/1M)	87dB	88dB
Maximum SPL (Pmax/1M)	91.4dB	92.3dB
Driver Impedance	8 Ohms	8 Ohms
Magnet	10 oz. ferrite	10 oz. ferrite
Frequency Response Range	57Hz ~ 20kHz	34Hz ~ 20kHz
Dispersion @ 1000Hz	120° Conical	120° Conical
Drivers	5.25" Polypropylene woofer 1" Mylar tweeter	6.55" Polypropylene woofer 1" Mylar tweeter
Speaker Dimensions	9.43" (Dia.) x 6.12" (D)	11.02" (Dia.) x 7.58" (D)
Mounting Dimensions	8.38" (Dia.)	9.88" (Dia.)
Weight	4.5lbs	5.5lbs
Material	Baffle: Fire-resistant ABS Backcan: Fire-resistant ABS Grille Material: Metal	Baffle: Fire-resistant ABS Backcan: Fire-resistant ABS Grille Material: Metal
Color	Off-White or Black	Off-White or Black

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines