

SP6MAWT 6.5" off-white housing**Features**

- ABS flame retardant back can
- Easy select transformer dial
- 25V or 70V selector switch
- Safety loop for additional mounting security
- Ported bass
- NDAA Compliant*

Speaker Specifications

Model	SP6MAWT
RMS Power	40W
Max Power	80W
Transformer Type	70/25V (selectable)
Transformer Power Taps	40W, 30W, 15W, 7.5W, 5W, 2.5W, 1W, 0.5W, 0.25W, & 8 Ohms
Termination Type	Press terminal
Sensitivity (1W/1M)	89dB
Maximum SPL (Pmax/1M)	106dB
Driver Impedance	8 Ohms
Magnet	10 oz. Neodymium
Frequency Response Range	50Hz ~ 20kHz
Dispersion @ 1000Hz	120° Conical
Drivers	6.5" Fiberglass woofer 1" Titanium tweeter
Speaker Dimensions	8.63" (W) x 12" (H) x 4.25" (D)
Mounting Dimensions	7.5" (W) x 10.75 (H)
Weight	5.5lbs
Material	Baffle: Fire-resistant ABS Backcan: Fire-resistant ABS Grille: Metal
Color	Off-white



Sold individually

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines