


SCP PART#: 22/4COIL-XX

4C/22 AWG STRANDED BC, COIL PACK, UL CMR PVC JKT - 500 FT COIL



Part Number: Jacket Color:

22/4COIL-BK	Black
22/4COIL-BL	Blue
22/4COIL-BN	Brown
22/4COIL-GN	Green
22/4COIL-GY	Gray
22/4COIL-OR	Orange
22/4COIL-WT	White
22/4COIL-YL	Yellow

Standard: UL 444 & UL 13, Type (UL) CMR/CL3 c(UL)
EU RoHS 2011/65/EU Compliant

Construction Characteristics:

Conductor	Material	Bare Copper
	Size	22AWG X 4C
	Construction	7/0.25+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.18mm
	AVG.Thickness	0.20mm
	Diameter	1.1+/-0.05mm
	Colors	Black & Red & White & Green
Jacket	Material	PVC
	Min.Thickness	0.30mm
	AVG.Thickness	0.40mm
	Diameter	3.5+/-0.20mm
	Rip Cord	Nylon
	Color	Varies
Bend radius	Min 15D/55mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C		
Minimum installation temperature	0°C + 40°C		
Conductor Resistance(22AWG)	Max 53.5ohm/km at 20°C		
Dielectric Strength	Min AC1.5KV		
Insulation Resistance	Min 50MΩ*km at 20°C		
Rated Voltage	Max 300Volts		
Marking:			
STRUCTURED CABLE PRODUCTS --- 22/4COIL --- SECURITY CABLE UNSH 4C 22 AWG STRANDED--- E198134 SCP3 (UL)C(UL) CMR ---PVC JKT RoHS EC ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 XXXFEET			
Packaging:			
Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
3.4kgs	250x50x250	500ft/COIL	150