

Features

- Provides uninterrupted power
- Distinctive alarms for on battery and battery low

Description

The PK250B Uninterruptible Power Supply (UPS) provides uninterrupted power in the event of utility power failures, brownouts and blackouts. The PK250B is for use with the NC356CE Central Equipment (CE) Module, NC455CE Central Equipment (CE) Module, NC435G3 Tek-CARE® Hub, NC331 Tek-CARE® Hub, NC503 Central Monitoring Dialer, and the NC475 Tek-CARE® Central Equipment. Its economical cost and compact size will enhance the operation of your system.

When power is interrupted, the PK250B immediately cuts in to provide square wave power for any connected hardware until an emergency generator is activated or power is restored. In the event of a prolonged power outage, the PK250B will provide power to the limit of its battery. Battery backup for the NC475 Tek-CARE Central Equipment is rated for 10 minutes.

The unit has distinctive alarms for *on battery* and *battery low*. Other features include output receptacles for connection of equipment, and power cord for a standard 120 volt, 15 AMP power circuit.

Applicable Components

NC356CE Central Equipment Module (Tek-CARE300III Nurse Call System)
NC455CE Central Equipment Module (Tek-CARE400 P5+ Nurse Call System)
NC435G3 (Tek-CARE400 GEN3 Nurse Call System)
NC331 (Tek-CARE3000 Nurse Call System)
NC475 Tek-CARE Central Equipment



PK250B Uninterruptible Power Supply (UPS)

Specifications

Dimensions:	5.5"H × 10.8"W × 4.1"D (139.7 mm × 274.3 mm × 104.1 mm)
Battery:	
Type:	Sealed, maintenance-free lead-acid
Capacity:	600 VA / 330 W
Voltage:	115 VAC +/-8%
Frequency:	50 or 60 Hz +/-0.1% (auto-sensing)
Connections:	5x 115 VAC battery backup + surge 2x 115 VAC surge protection only 1x USB battery backup + surge
Input:	
Voltage:	120 VAC
Frequency:	50 or 60 Hz
Connection:	5' cord with right angle plug

Listings



FCC Part 15 Class B.



UL 2560 Listed; UL® File Number E71599.