



The Turing Smart Series decoders display IP video channels over the network onto one or more video monitors. They are intended to be used in conjunction with other Smart Series cameras and NVRs.

KEY FEATURES

- Managed by Smart Station software (Windows)
- Dual HDMI simultaneous video output
- Decoding resolution up to 8K
- Support VGA and SDI video output
- Supports up to 64 split screens for single output



SPECIFICATIONS

MODEL NUMBER		TF-DEC01E
		
VIDEO OUTPUT		
No. of Output	1	
Decoding Capability	1-ch 8K@60fps、2-ch 8K@30fps、8-ch 12MP@20fps、8-ch 3840*2160@30fps、32-ch 1080P@30fps、64-ch 720P@30fps	
Split Screen	Up to 64	
Video Format	H.265, H.264, MPEG4, MJPEG	
HDMI Output	7680*4320@60Hz, 1920*1080@60Hz, 1660*1200@60Hz, 1280*720@60Hz, 1024*768@60Hz	
VGA Output	1920*1200@60Hz, 1920*1080@60Hz, 1280*720@60Hz, 1024*768@60Hz	
SDI Output	1920*1080@60Hz、1920*1080@50Hz、1280*720@60Hz、1280*720@50Hz	
Output Mode	Simultaneous (All outputs identical)	
INTERFACE		
Video Interface	2 x HDMI, 1 x VGA, 1 x SDI	
Ethernet	1 x RJ-45 , 10M/100M/1000M adaptive Ethernet Interface	
SFP	2 x Gigabit optical port	
USB	4 x USB 3.0	
GENERAL		
Dimensions (WxDxH)	177mm × 191 mm × 40mm	
Operating temperature	-10~60℃	
Operating humidity	5% ~ 95%(No-condensing)	
Power supply	12V DC	
Weight	2kg	
Power consumption	15W	