

DELIVERIES SO FAST, YOU'LL THINK WE BURNED RUBBER

(Don't worry we didn't)



**Channel
Prime Alliance**
a RAVAGO Company



**CPA
Canada**
a RAVAGO Company



The information contained herein is based upon laboratory tests believed to be reliable. However, it is offered solely for guidance to persons who will make their own determination. Ravago products are sold without warranty, expressed or implied.


BUTYL	Mooney Viscosity 1+8 @ 125°C	Unsaturation	Halogen
G&E Blended Butyl	45 ± 10	Medium	–
G&E Blended Bromobutyl	35 ± 10	–	2.0 ± 0.6
G&E Blended Chlorobutyl	40 ± 10	–	1.1 ± 0.2
G&E Blended PMSB	40 ± 10	–	0.9 - 2.0
G&E Blended HIR	40 ± 15	–	0.7 - 2.1


EPDM	Raw Polymer Viscosity 1+4 @ 125°C	Ethylene Content	ENB	Comments
G&E 465-75	45 ± 10	Medium	Medium	75 part oil-extended, nonstaining plasticizer.
G&E Non-Oil Extended	45 ± 15	High	Medium	High ethylene, excellent for extruded and molded goods.
G&E 565	50 ± 10	High	High	High ethylene, recommended for high quali- ty extruded or molded goods.
G&E 254	30 ± 10	Medium	Medium	Low mooney, high green strength polymer, excellent for injection & transfer molded products

SBR MASTERBATCH	Black		Oil		Tensile	Elong %	300% Modulus	Duro	Specific Gravity
	Parts	Type	Parts	Type					
G&E 1605	50	500 Series	N/A	N/A	3000	350	2500	65	1.13
G&E 1606	52	300 Series	10.00	HA	3200	450	2000	65	1.13
G&E 1805	75	330 Series	37.50	N	2600	350	1500	60	1.13
G&E 1815	75	300 Series	50.00	N	2500	500	1200	55	1.14
G&E 1847	75	300 Series	50.00	HA	2500	650	1000	60	1.14
G&E 1848	82.5	300 Series	62.50	HA	2500	600	1000	60	1.17

SSBR	Mooney Viscosity	Styrene	Vinyl	Non- Aromatic Oil	Stabilizer
G&E 465-75	45 ± 10	Medium	Medium	37.5 Parts	Staining
G&E Non-Oil Extended	45 ± 15	High	Medium	-	Staining

Ready for the rubber to hit the road? So are we. With a diverse product offering and a dedicated team of specialists, we can help you meet all of your elastomer needs.

 DOW EPDM	Mooney Viscosity, ML 1+4 at 125°C (ASTM D 1646)	Ethylene, Mass % (ASTM D 3900)	ENB, Mass % (ASTM D 6047)	MWD Characteristics (Dow Test Method)
NORDEL 3430	27	42	0.7	Narrow
NORDEL 3640	40	55	1.8	Medium
NORDEL 3720P	20	70	0.6	Broad
NORDEL 3722P	18	71	0.5	Medium
NORDEL 3745P	45	70	0.5	Narrow
NORDEL 3760P	63	67	2.2	Medium
NORDEL 3765 XFL	65	67	2.5	Broad
NORDEL 4520	20	50	4.9	Medium
NORDEL 4570	70	50	4.9	Medium
NORDEL 4571 XFM	70	47	4.9	Broad
NORDEL 4640	40	55	4.9	Medium
NORDEL 4725P	25	70	4.9	Broad
NORDEL 4760P	60	67	4.9	Medium
NORDEL 4770 P	70	70	4.9	Medium
NORDEL 4771 XFL	70	71	4.9	Broad
NORDEL 4785HM	85	68	4.9	Medium
NORDEL 4820P	20	85	4.9	Narrow
NORDEL 5565	65	50	7.5	Medium
NORDEL 6530 XFC	30	55	8.5	Broad
NORDEL 6555 OE	55	53	8.5	Medium
NORDEL 6565 XFC	65	55	8.5	Broad
Typical Properties and Applications of NORDEL™ Hydrocarbon Rubber				
Suffix designation: P = sold only as pellets; R = sold only as rods; No suffix = bale form				

 TRINSEO.		Mooney Viscosity (ASTM D 1646)	Bound Styrene (ASTM D 5775)	Styrene Content (SM ² , FTIR)	Cis-1,4 content (SM ³ , FTIR)	Specific Gravity (SM ³)
BR	Buna [®] cis 132	45.0			95	
BR	SE PB 3501	45.0			45	
BR	SE PB 5800	51.0			37	
ESBR	Buna [®] SB 1500	50.0	23.5			0.93 g/cm ³
ESBR	Buna [®] SB 1502	50.0	23.5			0.93 g/cm ³
ESBR	Buna [®] SB 1723	50.0	23.5			0.93 g/cm ³
ESBR	Buna [®] SB 1739	53.0	40.0			0.95 g/cm ³
SSBR	SPRINTAN [®] SLR 4601	50.0		21.0		0.93 g/cm ³
SSBR	SPRINTAN [®] SLR 4602	65.0		21.0		0.93 g/cm ³
SSBR	SPRINTAN [®] SLR 4630	55.0		25.0		0.94 g/cm ³
SSBR	SPRINTAN [®] SLR 6430	67.0		40.0		0.95 g/cm ³

WE HELP CREATE PRODUCTS,
NOT PROBLEMS.

channelpa.com

Channel Prime Alliance
1803 Hull Avenue
Des Moines, IA 50313 | U.S.A.
800.247.8038

CPA Canada
180 Attwell Drive, Suite 260
Toronto, Ontario M9W-6A9 | Canada
888.777.4390

CPA de México
Leibnitz No. 11 Int. 104, Col. Anzures
Del. Miguel Hidalgo, C.P. 11590 | MÉXICO, D.F.
55.2624.0089