

# SmartDip

WIRELESS

## Datasheet

- View tank levels from anywhere in the world
- Easily to install
- Automate alerts for easy inventory management



Scan for  
more details



## Specifications

|                        |  |   |
|------------------------|--|---|
| Size                   | Height: 77 mm  | Width: 141 mm (including lid)<br>Body width: 107 mm |
| Accuracy               | 0.25% FS (Max) 0.5% FS (Typical)   |   |
| Operating Temperature  | -25 °C to 70 °C  |   |
| Battery Life           | 5 Years, longer when exposed to daily sunlight. (Based on one dip per day) |   |
| Recommended Fuel Types | Diesel, DEF(AdBlue) and other non-hazardous liquids (water, oil)           |   |
| Tank Height            | up to 10m  |   |
| Cable                  | Polyethylene Ventilated Cable, cable is 5m longer than height              |   |
| Tank Thread Size       | 2" BSP   |   |
| Dips per Day           | 1 - 4 (Configurable)   |   |
| View data              | FMT Webportal, Mobile phone via QR code                                    |   |
| Alerts                 | Via Email; Offline, Low, High & Scheduled Summary                          |   |

## Comparison Table

| Feature                   | SmartDip              | Wireless SmartDip               |
|---------------------------|-----------------------|---------------------------------|
| Data Update Frequency     | Real-time             | 1-4 dips per day                |
| Number of Tanks per Unit  | Up to 8 tanks         | 1 tank                          |
| Configurable Alarms       | Real-time             | Delayed until dip is taken      |
| Record Fuel Deliveries    | Yes                   | No                              |
| Power Source              | Wired (SmartFill FMS) | Battery and Solar               |
| Battery Life              | N/A                   | Up to 5 years (1 dip per day)   |
| SmartFill FMS Integration | Yes                   | No                              |
| ATEX/IECEx Rating         | Yes (optional)        | No                              |
| Maintenance Requirements  | None                  | Battery Replacement as required |

Need more information?  
Get in contact with us

Office: (08) 8240 5585  
Email: [sales@fmtweb.com](mailto:sales@fmtweb.com)

Fluid Management Technology Pty Ltd  
147-149 William St, Beverley SA 5009

