





SmartDip

WIRELESS

Datasheet

-  View tank levels from anywhere in the world
-  Easy to install
-  Automate alerts for easy inventory management



Scan for
more details



Specifications

Size	Height: 1.5 in	Width: 5.55 in (including lid) Body width: 4.21 in
Accuracy	0.25% FS (Max) 0.5% FS (Typical)	
Operating Temperature	-13 °F to 158 °F	
Battery Life	5 Years, longer when exposed to daily sunlight. (Based on one dip per day)	
Recommended Fuel Types	Diesel, DEF(AdBlue) and other non-hazardous liquids (water, oil)	
Tank Height	up to 394 inches	
Cable	Polyethylene Ventilated Cable, cable is 5m longer than height	
Tank Thread Size	2" NPT	
Dips per Day	1 - 4 (Configurable)	
View data	FMT Webportal, Mobile phone via QR code	
Alerts	Via Email; Offline, Low, High & Scheduled Summary	

Comparison Table

Feature	SmartDip	Wireless SmartDip
Data Update Frequency	Real-time	1-4 dips per day
Number of Tanks per Unit	Up to 8 tanks	1 tank
Configurable Alarms	Real-time	Delayed until dip is taken
Record Fuel Deliveries	Yes	No
Power Source	Wired (SmartFill FMS)	Battery and Solar
Battery Life	N/A	Up to 5 years (1 dip per day)
SmartFill FMS Integration	Yes	No
ATEX/IECEX Rating	Yes (optional)	No
Maintenance Requirements	None	Battery Replacement as required

Need more information?
Get in contact with us

Office: 1800 569 8704
Email: sales.us@fmtweb.com

Fluid Management Technology LLC
25235 Dequindre Rd, Madison Heights, MI 48071

