




SmartFill

LITE

Datasheet

-  Cloud based fuel management system
-  Accurate reporting of fuel use and tank levels
-  Built for tough and harsh conditions



Scan for
more details

Specifications

Size and Weight	Height: 240 mm Width: 240 mm Depth: 141 mm	Weight: 2.6 kg
Enclosure Construction	Automotive grade glass reinforced nylon	
Display	5" TFT High Brightness Display, 800x480 resolution	
Keypad	Vandal resistant 16 key, stainless steel buttons	
Operating Temperature	-20 °C to +70 °C	
Power Requirements: AC	90~250VAC-0.6A@115VAC 0.4A@230VAC	
Power Requirements: DC	9.4-36VDC-1.8A@12VDC	
Pulser Input	Reed switch or Hall Effect, pulse input 5-12VDC	
Pumps Supported	Mechanical pump and flow meter	
Relay Switching Capability	AC switching 240VAC 10A, DC switching 24VDC 5A	
Nozzle Authorisation	Normally Open Nozzle Switch or Walk Time	
DC Power Delay Switch	Momentary NO push buttons, 36VDC, 2A	
Readers	Included: NFC reader Optional: Reader Wand	
Tank Gauging <small>(optional)</small>	SmartDip	
USB	USB2.0 typeA interface included	
4G LTE	LTE FDD RF band: 1, 2, 3, 4, 5, 7, 8, 9, 12, 13, 14, 18, 19, 20, 25, 26, 28 HSPA+ band: 1, 2, 4, 5, 6, 8, 19	
Mounting options	Included: Wall, base and flush mount fixing	
Installation Requirement	To be installed outside of the hazardous zone for flammable liquids such as gasoline and E85	

Need more information?
Get in contact with us

Office: (08) 8240 5585
Email: sales@fmtweb.com

Fluid Management Technology Pty Ltd
147-149 William St, Beverley SA 5009

