

# SmartFill

OUTDOOR PAYMENT TERMINAL

## Datasheet

- ⌚ Outdoor payment terminal for 24/7 fuel sales
- 〝 Built for tough and harsh conditions
- 🌐 Monitor sales from anywhere in the world



Scan for  
more details



## Specifications

Size and Weight	Height: 700 mm Height with hood: 732 mm Pedestal height: 1000 mm	Width: 400 mm Width with hood: 403 mm Depth: 230 mm	Weight: 22.75 kg
Enclosure Construction	316 Grade Stainless Steel and automotive grade glass reinforced nylon		
Display	Marine Grade-7.0" WVGA TFT-LCD display, 800x480 resolution		
Keypad	Vandal resistant 16 key, stainless steel buttons		
Operating temperature	-20°C to 70°C		
Power Requirements: AC	85~264VAC-1.6A@100Vac		
Pumps Supported	Mechanical pump and flow meter (1-4 pumps); Electronic (1-8 pumps): Gilbarco, Compac, Wayne Dart, Wayne CL, Tatsuno, Tokheim, PEC		
Readers	NFC, magnetic stripe and credit card		
Ethernet	10/100 Mbps		
4G LTE	LTE FDD RF band: 1, 2, 3, 4, 5, 7, 8, 9, 12, 13, 14, 18, 19, 20, 25, 26, 28 HSPA+ band: 1, 2, 4, 5, 6, 8, 19		
Mounting Options	Included: Wall, base and flush mount fixings included; Optional: Pedestal		
Installation Requirement	To be installed outside of the hazardous zone for flammable liquids such as gasoline and E85		
Printer	Industrial thermal printer, 58 mm to 60 mm wide x 100mm roll diameter.		
EMV Payment Hardware	Ingenico Self/5000 Payment Terminal, PCI PTS 5.x Compliant		
Card Acceptance	Visa, MasterCard, Account cards (white cards), Apple Pay, Google Pay, SmartFill NFC cards and Fobs, WEX		
Tank Gauging (optional)	SmartDip or TLS Interface		
Certifications	 <b>AT&amp;T</b>  <b>verizon</b> <sup>®</sup>   (Weights & Measures № 25-068)  <b>NMI</b> S559		

Need more information?  
Get in contact with us

Office: (08) 8240 5585  
Email: [sales@fmtweb.com](mailto:sales@fmtweb.com)

Fluid Management Technology Pty Ltd  
147-149 William St, Beverley SA 5009

