

SmartFill

OUTDOOR PAYMENT TERMINAL

Datasheet

- Outdoor payment terminal for 24/7 fuel sales
- Built for tough and harsh conditions
- Monitor sales from anywhere in the world



Scan for
more details



Specifications

Size and Weight	Height: 27.56 in Height with hood: 28.8 in Pedestal height: 39.37 in	Width: 15.75 in Width with hood: 15.9 in Depth: 9.05 in	Weight: 50.15 lb
Enclosure Construction	316 Grade Stainless Steel, automotive grade glass reinforced nylon		
Display	Marine Grade-7.0" WVGA TFT-LCD display, 800x480 resolution		
Keypad	Vandal resistant 16 key, stainless steel buttons		
Operating temperature	-4°F to 158°F		
Power Requirements: AC	85~264VAC-1.6A@100Vac		
Pumps Supported	Electronic (1-8 pumps): Gilbarco, Wayne Dart, Wayne CL, Bennet, Tatsuno, Tokheim		
Readers	Inbuilt NFC reader, magnetic stripe		
Ethernet	10/100 Mbps		
4G LTE	LTE FDD RF band: 1, 2, 3, 4, 5, 7, 8, 9, 12, 13, 14, 18, 19, 20, 25, 26, 28 HSPA+ band: 1, 2, 4, 5, 6, 8, 19		
Mounting Options	Included: Wall, base and flush mount fixings included; Optional: Pedestal		
Installation Requirement	To be installed in an unclassified location as defined by NEC Article 500, where no hazardous (classified) atmosphere is expected to be present under normal operating conditions		
Printer	Industrial thermal printer, 2.28 inches to 2.36 inches wide x 4 inch roll diameter.		
EMV Payment Hardware	Ingenico Self/5000 Payment Terminal, PCI PTS 5.x Compliant		
Card Acceptance	Visa, MasterCard, Account cards (white cards), Apple Pay, Google Pay, SmartFill NFC cards and Fobs, AMEX		
Tank Gauging (optional)	SmartDip or TLS Interface		
Certifications	   (Weights & Measures № 25-068) 		

Need more information?
Get in contact with us

Office: 1800 569 8704
Email: sales.us@fmtweb.com

Fluid Management Technology LLC
25235 Dequindre Rd, Madison Heights, MI 48071

